

# Classic form with exemplary detail

Day-Brite Rubato, comfortable contemporary lighting within your reach

**PHILIPS**

**Day-Brite**

# Soft, smooth, comfortable

Achieving comfortable and contemporary lighting need not be expensive. Day-Brite's Rubato is the perfect solution for spaces that require glare free illumination at a reasonable cost without sacrificing performance or aesthetics. The classic rounded form and matte white finish complement a wide range of modern interiors.

## Details

Rubato can be suspended by aircraft cables from a variety of ceiling types for indirect or direct/indirect applications. Direct/indirect versions provide a unique and interesting "checkerboard" perforation pattern or lower baffled openings while retaining economical formed steel construction. The wide, smooth light distribution and 18" minimum recommended suspension distance allow wide luminaire spacing. The perforations, baffles and diffusers used in direct/indirect Rubato variations allow just enough downlight to provide smooth illumination and promote a pleasing appearance, while directing the majority of the light upward to provide a soft, glare free environment. A version is also available utilizing a solid lower housing to provide 100% uplight for installations where purely indirect lighting is desired. In all variations, Rubato supplies soft, smooth, comfortable illumination that integrates with any architecture.

**Matte white finish provides a soft, architectural appearance.**






Die-cast aluminum end caps provide durability with consistent fit and finish.

Unique “checkerboard” perforation pattern creates an interesting yet subtle visual contribution to any area.





Formed steel housing is rounded for classic, versatile aesthetics.

**Indirect**



**Direct/Indirect**



Center lamps are situated diagonally to provide even illumination while allowing room for cable mounting.



Small 3" x 9" profile prevents the luminaire from visually overpowering smaller spaces.

**Availability**

Rubato is available in 4, 8, and 12 foot lengths with 1, 2, or 3 lamp cross sections for individual or row mounting. Row mount units are pre-wired in 1, 2, or 3 circuit configurations with quick-connect plugs for fast and simple electrical connections. Cable hangers are available for many ceiling variations to provide the utmost in flexibility. Standard configurations and quantities are available for shipment within 10 days to maximize convenience.

SAMPLE CATALOG NUMBER: **ROSP1C232-24-UNV-48SCM1**

<p><b>Family</b> RO – Rubato</p>	<p><b>Light Distribution</b>  <b>P</b> – Direct/Indirect micro-perforated housing  <b>S</b> – Indirect only  <b>O</b> – Direct/Indirect bottom openings with baffles</p>	<p><b>No. of Lamps/ Cross Section</b> (not included)  <b>1</b>  <b>2</b>  <b>3</b>  <b>4</b></p>	<p><b>Run Length</b>  <b>4</b> – 4'  <b>8</b> – 8'  <b>12</b> – 12'          Multiples of 4' (16, 20, 24, etc)</p>	<p><b>Max. Suspension Distance</b>  <b>24</b> – 24" max.  <b>48</b> – 48" max.  <b>72</b> – 72" max.  <b>96</b> – 96" max.</p>	<p><b>Ceiling Mount</b>  <b>M1</b> – Support connection at ceiling  <b>M2</b> – Support connection above ceiling  <b>M3</b> – Support connection to structure  <b>M5</b> – Support connection to T-bar  <b>M6</b> – Non-seismic support connection to T-bar</p>	<p><b>Options</b>  <b>1E7</b> – 1 emerg. ballast/row (635 lumens)  <b>2E7</b> – 2 emerg. ballasts/row (635 lumens)  <b>CM</b> – Canadian Market  <b>DC</b> – Dust cover(s)  <b>LPT735</b> – Installed lamps 70+ CRI 3000K  <b>LPT835</b> – Installed lamps 80+ CRI 3500K  <b>LPT841</b> – Installed lamps 80+ CRI 4100K  <b>GLR</b> – Fusing</p>
<p><b>Type</b>  <b>S</b> – Suspended  <b>W</b> – Wall Mount</p>	<p><b>Wiring</b>  <b>1C</b> – 1 Circuit  <b>2C</b> – 2 Circuit  <b>3C</b> – 3 Circuit  <b>1D</b> – 1 Circuit Dimmin  <b>1E</b> – 1 Circuit + Emergency  <b>2E</b> – 2 Circuit + Emergency</p>	<p><b>Lamp Type/Wattage</b>  <b>28</b> – 28wT5 (46")  <b>32</b> – 32wT8 (48")  <b>54HO</b> – 54wT5HO (46")</p>	<p><b>Voltage</b>  <b>120</b>  <b>277</b>  <b>347</b>  <b>UNV</b> – Universal voltage, 120-277 volt</p>	<p><b>Power Cord</b>  <b>CC</b> – Coiled Cord  <b>SC</b> – Straight Cord</p>		



©2010 Philips Day-Brite  
 All rights reserved.  
 776 South Green Street • Tupelo, MS 38804  
 p. 800.234.1890 • f. 662.841.5501  
 Canadian Division  
 189 Bullock Drive • Markham, Ontario L3P 1W4  
 p. 905.294.9570 • f. 905.294.9811

**PHILIPS**  
**Day-Brite**

Form No. **132**  
 Rev. 0110CT.5M  
 www.daybrite.com



This brochure was printed on FLO recycled paper.  
 FLO is an environmentally responsible paper containing 10% Post Consumer Waste. FLO is 3rd party certified to come from a well managed forest.