



realistic change

Philips Capri 6" LED Retrofit/New Construction Luminaires.

Making it simple to make a real difference.

PHILIPS
capri

CRL6K-G2

6" LED Module, Retrofit/New Construction



CRL6K-G2
LED Retrofit/New Construction Module

The Philips Capri CRL6K-G2 is the ideal solid state solution for retrofit and new construction applications.

- Consumes less than 13 watts of energy.
- Energy-saving, long life LED technology produces lumens and distribution equal to a 65W BR30 lamp.
- Long life LEDs designed to perform up to 50,000 hours with 70% lumen maintenance.
- LED Module mounts easily into incandescent housings with torsion springs providing a secure fit to the ceiling.
- Wide choice of accessory finishing splays, reflectors and baffles, in a variety of finishes to complement any decor.
- Standard frosted lens provides soft comfortable light.
- **Dimmable with standard triac and electronic low voltage dimmers (see spec sheet for complete list of recommended dimmers).**
- cETL classified in wet locations for IC, non-IC, and AirSeal™ applications.
- Classified for use in Philips Capri and many other competitors' fixtures. (See specification sheet for details)
- Tested to IESNA LM-79 photometric standard. Lumen maintenance based on Philips Lumiled LM-80 data.
- Energy Star qualified, California T24 compliant, Title 20 Listed.
- **2700 CCT**
- 5 year warranty for both IC and Non-IC applications.

Available Splays

Splay Dimensions: 5-3/8" I.D. (137mm) X 7-1/2" O.D. (191mm) Splays ordered separately.



CRL6R-WHT
White Reflector,
Spun Aluminum



CRL6R-BLK
Black Reflector,
Spun Aluminum



CRL6R-CLR
Clear Specular Reflector,
Spun Aluminum

Ordering is easy. Catalog numbers begin with the LED retrofit module listed below, followed by options and splay as shown.

LED Module	Lumens	Color Temperature	Voltage	Splay	Style	Finish
CRL6K-G2	6	27K	BLANK	CRL6	R	WHT
6" LED Module	600 lumens	2700 Kelvin	120 Volt	6" LED Module	Reflector	White
Generation 2	nominal			Splay Insert ²	B Baffle ¹	BLK Black
						CLR Clear
						GLD Gold

Example: CRL6K-G2-6-27K CRL6B-WHT

1. Baffle available in white or black only.
2. CRL6K-G2 module and accessory splay ordered and shipped as separate line items.

No voltage designation is required when building a catalog number (see ordering example above). All Philips Capri LED retrofit modules are 120 volt.

NOTE: The Philips Capri LED Retrofit Module is compatible with multiple triac and electronic low voltage dimmers. See spec sheet for complete listing.

CR1QP-LED-G2

6" New Construction Housing

The CR1QP-LED-G2 is designed for new construction, high efficacy LED applications.

- CRL6KQP-LED-G2 recessed 6" housing is ETL Listed for use with the CRL6K-G2 module and marked for 13W maximum input power.
- Includes quick connectors for fast easy installation.
- Installation is compliant to California Title 24 - 2008.
- Ideal choice for applications requiring lighting power density calculations (LPD, W/ft²) such as LEEDs and ASHRAE 90.1.
- Omission of the lamp holder in the CR1QP-LED-G2 guarantees long-term, high-efficacy lighting.
- cETL listed for IC, non-IC, and AirSeal™ applications.



CR1QP-LED-G2
New Construction IC/ Non-IC Rated Housing for High-efficacy applications



CR1QP-LED-G2 comes standard with Quick Connectors for easy installation.



Simply remove Edison adapter from CRL6K-G2 module and insert wires into Quick Connectors on * for a high efficacy installation.



Gently push CRL6K-G2 module into the downlight allowing torsion springs to guide and secure module.



CRL6R-GLD
Gold Reflector,
Spun Aluminum



CRL6B-WHT
White Baffle,
Spun Aluminum



CRL6B-BLK
Black Baffle,
Spun Aluminum

Ordering is easy. Catalog numbers begin with the housing listed below, followed by the LED Module and splay as shown.

Housing	LED Module	Lumens	Color Temperature	Voltage	Splay	Style	Finish
CR1QP-LED-G2 6" recessed housing for LED Generation 2	CRL6K-G2 6" LED module Generation 2	6 600 lumens nominal	27K 2700 Kelvin	BLANK 120 Volt	CRL6 6" LED Module Splay Insert ²	R Reflector B Baffle ¹	WHT White BLK Black CLR Clear GLD Gold

Example: CR1QP-LED-G2 CRL6K-G2-6-27K CRL6B-WHT

1. Baffle available in white or black only.

2. CR1QP-LED-G2, CRL6K-G2 module and accessory splay are ordered and shipped as separate line items.

No voltage designation is required when building a catalog number (see ordering example above).

All Philips Capri LED retrofit modules are 120 volt.

PHILIPS capri

776 South Green Street
Tupelo, MS 38802
p. 662.842.7212
f. 662.841.5501
www.caprilighting.com

189 Bullock Drive
Markham, Ontario L3P 1W4
p. 905.294.9570
f. 905.294.9811
www.day-britecanada.com



This brochure was printed on FLO recycled paper:
FLO is an environmentally responsible paper
containing 10% Post Consumer Waste.

FLO is 3rd party certified to come from a well
managed forest.



©2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Document order number: C31.0911.CT2.5M